

SIDEWINDER®

HIGH-IMPACT, WATERPROOF MILITARY LIGHT
WITH ARTICULATING HEAD

The Sidewinder meets a variety of hands-free illumination requirements with various color LEDS each with different outputs. 185° articulating head aims the beam.

Designed for easy mode selection even with gloved hands.

Meets MIL-STD-810F, METHOD 512.4.





back of helmet

Attaches to MOLLE with pocket clip or MOLLE strap

One switch for On-Off, dimming and mode selection functions Pull-to-turn locking rotary color selector knob with tactile indicator for easy operation with gloves

Powered by two "AA" alkaline batteries (included)

Also accepts two "AA" lithium batteries for extended operation in extreme temperatures (-40° F to +150°F)

Battery polarity indicators for easy replacement in the dark



Unbreakable, gasket-sealed polycarbonate lens with scratch-resistant coating



Cord attachment hole supports up to 25 lbs.



extra security from loss of light and allows it to be worn around the neck

Rugged nylon polymer body is virtually indestructible

Tethered tailcap prevents loss

MILITARY MODEL (WHITE, RED, BLUE, IR LEDS)						
PART#	NSN/MCN#	DESCRIPTION	C00	TAA		
14000	6230-01-556-0487	W/ALKALINE — CLAM PACKAGED. COYOTE.	US	YES		
14027	6230-01-571-8752	W/ALKALINE — WITH HELMET MOUNT. CLAM PACKAGED. COYOTE.		YES		
14031	-	W/ALKALINE — WITH E-MOUNT. CLAM PACKAGED. COYOTE.	US	YES		

AVIATION MODEL (WHITE, GREEN, BLUE, IR LEDS)						
PART#	NSN/MCN#	DESCRIPTION	C00	TAA		
14008	-	W/ALKALINE — CLAM PACK- AGED. COYOTE.	US	YES		
14024	6230-01-572-6216	W/ALKALINE — WITH HELMET MOUNT. BOXED PACKAGED. COYOTE.	US	YES		

SIDEWINDER® LIGHT OUTPUT & BATTERY RUN TIME						
LED	Light Output	Low 5% Output	Medium 1 25% Output	Medium 2 60% Output	High 100% Output	Strobe 100% Output
White	55 Lumens	100 Hrs+	45 Hrs	11 Hrs	5.5 Hrs	10 Hrs
IR	25mW/sr (min) radiant intensity	200 Hrs+	140 Hrs	60 Hrs	24 Hrs	40 Hrs
Red	1 Lumens	200 Hrs+	140 Hrs	60 Hrs	24 Hrs	40 Hrs
Blue	1.8 Lumens	150 Hrs+	100 Hrs	35 Hrs	16 Hrs	30 Hrs
Green	4.5 Lumens	150 Hrs+	100 Hrs	35 Hrs	16 Hrs	30 Hrs
All run time to 10% of initial output level. Illumination output electronically regulated.						

High-impact super tough nylon construction offers exceptional durability and weather resistance
IPX7 waterproof to 1m for 30 minutes; 3 meter multiple orientation impact resistance tested
2.34" (5.94 cm); 5.02 oz. (142g) [alk]; 4.38 oz. (124g) [lith]
Limited Lifetime Warranty Visit streamlight.com for full warranty information